

Application Reference No. 28/2023-24/51

(यह परीक्षण रिपोर्ट 30/04/2029 तक वैध है / THIS TEST REPORT IS VALID UPTO 30/04/2029)



Make of Agricultural Tractor
Model
Manufactured by

: JOHN DEERE
: 5050D 4WD V14
: M/s. John Deere India Pvt. Ltd.
Gat No.166 - 167 & 271 - 291,
Off. Pune - Nagar Road,
Sanaswadi, Taluka – Shirur, Pune -
412 208



भारत सरकार

कृषि एवं किसान कल्याण मंत्रालय
(कृषि एवं किसान कल्याण विभाग)

GOVERNMENT OF INDIA
MINISTRY OF AGRICULTURE AND FARMERS WELFARE
(DEPARTMENT OF AGRICULTURE & FARMERS WELFARE)

केन्द्रीय कृषि मशीनरी प्रशिक्षण एवं परीक्षण संस्थान

ट्रैक्टर नगर, बुदनी (म.प्र.) 466 445

CENTRAL FARM MACHINERY TRAINING & TESTING INSTITUTE

TRACTOR NAGAR, BUDNI (M.P.) 466 445

(An ISO 9001: 2015 Certified Institute)

T-1843/2374/2024	JOHN DEERE, 5050D 4WD V14 TRACTOR- INITIAL COMMERCIAL TEST
	THIS TEST REPORT IS VALID UPTO: 30/04/2029

IMPORTANT INFORMATION

The Government of India, Ministry of Agriculture and Farmers Welfare has directed, vide a OM No. 13-17/2021-M&T(I&P) dated 28.07.2022, that since 15th August, 2022, only mandatory tests will be carried out on a tractor unless applicant has expressly requested for optional tests as well, mentioned in the above captioned OM.

In the instant case, there is no request from the applicant to carry out the optional tests hence only Mandatory Tests, as given below, have been conducted and reported in this report: -

1. PTO performance
2. Hydraulic performance
3. Drawbar performance
4. Brake performance

Month: April	Test Report No.: T-1843/2374/2024	Year: 2024
--------------	-----------------------------------	------------



GOVERNMENT OF INDIA
CENTRAL FARM MACHINERY TRAINING & TESTING INSTITUTE
TRACTOR NAGAR, BUDNI (MADHYA PRADESH) 466445, INDIA
E-mail: fmti-mp@nic.in

Web site: <http://www.fmttibudni.gov.in>

Telephone: 07564-299003

CENTRAL FARM MACHINERY TRAINING AND TESTING INSTITUTE – BUDNI	Page 2 of 32
---	--------------

- [C] Tractor manufacturer's name and address : (i) **M/s. John Deere India Pvt. Ltd.**
Gat No.166 - 167 & 271 - 291, Off. Pune-Nagar Road, Sanaswadi, Taluka Shirur, Pune - 412 208
- (ii) **M/s. John Deere India Pvt. Ltd.**
Survey No. 501, Village - Khatamba Jamgod, Dewas Bhopal Highway, Dewas (Madhya Pradesh) - 455 115
- [C] Submitted for test by (applicant) : The Manufacturer
[C] Selected for test by : The Ministry vide OM No. 13-17/2021 - M&T (I&P) dated 28.07.2022, has allowed the applicant to submit the test sample directly to the Institute without requiring any random selection for Initial Commercial Testing. Thus, the applicant directly submitted the test sample to the Institute for test.
- [D] Place of running-in : At manufacturer's works
[D] Duration of running-in, (h):
-Engine : 20
-Transmission : 20
- [C] Location of test : Government of India,
Central Farm Machinery Training and Testing Institute, P.O. - Tractor Nagar,
BUDNI – 466445 (M.P.), INDIA

1. SPECIFICATIONS OF TRACTOR

- 1.1 Identification:**
- 1.1.1 Denomination**
- [C] Make of tractor : JOHN DEERE
[C] Model : 5050D 4WD V14
[C] Type : Four Wheel Driven, Standard Agricultural Tractor.
- [C] Month & year of manufacture : 11/23
[D] Country of origin : India
- 1.1.2 Numbers:**
- [D] 1st Serial No. or prototype : 1PY5050DEPF051946
[C] Serial No. : 1PY5050DKPA055310
- 1.2 Engine:**
- [D] Manufacturer's address : (i) **M/s. John Deere India Pvt. Ltd.**
Gat No.166 - 167 & 271 - 291, Off. Pune-Nagar Road, Sanaswadi, Taluka Shirur, Pune - 412 208
- (ii) **M/s. John Deere India Pvt. Ltd.**
Survey No. 501, Village - Khatamba Jamgod, Dewas Bhopal Highway, Dewas (Madhya Pradesh) - 455 115
- [C] Make : JOHN DEERE
[C] Model : 3029DPY106
[C] Type : Four stroke, liquid cooled, natural aspiration, direct injection, diesel engine
[C] Serial No. : PY3029D772512

6. SUMMARY OF OBSERVATIONS, COMMENTS & RECOMMENDATIONS

6.1 On the basis of test conducted the performance results have been summarized as evaluative (mandatory) / Non-evaluative (Non-mandatory) parameters applicable for Qualifying Minimum Performance criteria as per Clause-4 (Table-1) of IS: 12207-2022 for acceptance of the tractor for the purpose of subsidies/NABARD financing are summarized as under:

S. No.	Characteristic	Category (Evaluative / Non Evaluative)	Requirements as per IS: 12207-2022	Values declared by the applicant/ (D) Requirement (R)	As observed	Whether meets the requirements (Yes/No)
1	2	3	4	5	6	7
MANDATORY TESTS: (As per Ministry's Office Memorandum No. 13-17/2021-M&T (I&P) dated 28th of July, 2022).						
6.1.1	PTO Performance:					
a)	Maximum power under 2 h test, (kW) (Natural ambient condition)	Evaluative	Declared value to be achieved with a tolerance of: $\pm 5\%$ for PTO power and or engine power $> 26 \text{ kW} \pm 10\%$ for PTO power and or engine $\leq 26 \text{ kW}$.	30.3 (D)	31.1	Yes
b)	Power at rated engine speed, (kW)	Non Evaluative	-do-	30.0 (D)	31.1	Yes
c)	Specific fuel consumption corresponding to maximum power, (g/kWh)	Evaluative	Should not be more than 10% of declared value.	270 (D)	268	Yes
d)	Maximum equivalent crankshaft torque, (Nm)	Non Evaluative	$\pm 8\%$	186 (D)	172.1	Yes
e)	Back-up torque, percent	Evaluative	Should be min. 12%	12 (D) 12 (R) minimum	21.9	Yes
f)	Maximum operating temperature, ($^{\circ}\text{C}$):					
	1) Engine oil	Evaluative	The declared value should not exceed the <i>max.</i> value specified by the oil company and the observed value under natural ambient/high ambient condition should not exceed the declaration.	135 (D)	110	Yes
	2) Coolant	Evaluative	Observed value should not exceed the declared value or boiling point of coolant at radiator cap pressure whichever is lower. The boiling point of the coolant at radiator pressure shall be provided by the applicant.	120 (D)	101	Yes
g)	Engine oil consumption, (g/kWh)	Evaluative	Not exceeding 1% of SFC at max. Power under natural ambient conditions.	2.68 (R) maximum	0.16	Yes
h)	Smoke level, m^{-1}	Evaluative	Max Smoke level shall be reported out of 6 readings tested as per IS 12062 and observed value should be well within the required limits.	3.25 per meter (R) maximum	0.26	Yes

1	2	3	4	5	6	7
6.1.2	Drawbar performance:					
a)	Max. drawbar pull with ballast corresponding to 15 percent wheel slip, (kN)	Non Evaluative	Minimum 70% of static mass of tractor with ballast.	19.81 (D)	*	*
b)	Max. drawbar pull without ballast or with standard ballast corresponding to 15 % wheel slip or 7% track slip, (kN)	Evaluative	In case of tractors having total static mass \geq 1500 kg, Min 70% of static mass of tractor without ballast or with standard ballast, as the case may be. In case of light weight tractors having \leq 1500 kg total static mass of tractor, Min. 65% of static mass of tractor without ballast or with standard ballast, as the case may be.	13.77 (D) 13.73 (R) minimum	17.73	Yes
c)	Maximum drawbar power without ballast or with standard ballast as the case may be, (kW).	Evaluative	Minimum 80 % of PTO power as referred in SI No. i) a) of PTO performance in case of tractors having total static mass > 1500 kg. Minimum 75 % of PTO power as referred in SI No. i) a) of PTO performance in case of light weight tractors having \leq 1500 kg total static mass of tractor. Minimum 75 % of the engine power as referred in SI No. i) a) of engine performance in case of tractors which do not have a PTO shaft.	24.24 (D) 24.9 (R) minimum	26.2	Yes
d)	Maximum transmission oil temperature, (°C)	Evaluative	The declared value should not exceed the recommendation by the oil manufacturer. The observed value should not exceed the declared value throughout the drawbar test.	110 (D)	89	Yes

Remark (*): Applicant vide letter no. Nil dated 03.01.2024 has requested to conduct drawbar performance test under unballasted condition only which was allowed as per the additional guidelines for testing of tractors as per new regime of testing of tractors Ministry's Office Memorandum No. 13-14/2020-M&T (I&P) (82979) dated 28/08/2023. Accordingly, only unballasted drawbar performance test was conducted.

6.1.3 Power lift and hydraulic pump performance:						
a)	Maximum lifting capacity throughout the range of lift, (kN):					
	1)	At hitch points	Evaluative	Should not be less than 90% of declared value.	13.7 (D) 12.33 (R) minimum	15.04 Yes
	2)	With the standard frame	Evaluative	The lift capacity should at least be 24 kg/PTO kW and it should be 21.5 kg/engine kW where the tractor is not provided with a PTO shaft.	12.2 (D) 7.32 (R) minimum	12.64 Yes
b)		Maximum drop in the height of the point of application of the force after each 5 minutes interval for a total duration of 30 Minutes, (mm)	Non Evaluative	The observed value should not exceed 50 mm	50 (D) maximum	10 Yes

T-1843/2374/2024	JOHN DEERE, 5050D 4WD V14 TRACTOR- INITIAL COMMERCIAL TEST					
	THIS TEST REPORT IS VALID UPTO: 30/04/2029					

1	2	3	4	5	6	7	
6.1.4	Brake performance at 25 kmph:						
a)	Maximum stopping distance at a force, equal to or less than 600 N on brake pedal without ballast, (m):						
	1)	Cold brake	Evaluative	10	10 (R)	7.98	Yes
	2)	Hot brake	Evaluative	10	10 (R)	8.14	Yes
b)	Whether parking brake is effective at a force of 600 N at foot pedal (s) or 400 N at hand lever.	Evaluative	Yes / No	Yes	Yes	Yes	
6.1.5	OPTIONAL TESTS: As the applicant has not applied for any optional tests, therefore no optional tests was conducted.						
6.1.6	Safety features:						
a)	Guards against moving and hot parts	Evaluative	Belt drives, pulleys, silencer, hydraulic pipes [As per IS 12239 (Part2)]	Meets the requirement	Yes		
b)	Lighting arrangement	Evaluative	As per CMVR	Conforms	Yes		
c)	Seating requirements (Tractors having more than 1150 mm rear track width)	Non Evaluative	Should meet the requirements of IS: 12343 (As amended from time to time)	Does not meet the requirement	No		
d)	Technical requirements for PTO shaft	Non Evaluative	Should meet the requirements of IS: 4931 (As amended from time to time)	Conforms	Yes		
e)	Dimensions of three point linkage	Non Evaluative	Should meet the requirements of IS: 17231-2019 (Part-I) (As amended from time to time)	Does not meet the requirement	No		
f)	Specifications of linkage drawbar	Non Evaluative	Should meet the requirements of IS: 12953 (As amended from time to time)	Meets the requirement	Yes		
g)	Swinging drawbar (wherever fitted)	Non Evaluative	Should meet the requirement of IS: 12362 (Part 3) (As amended from time to time)	Not provided	Not applicable		
h)	Audible warning signal on tractor	Evaluative	If tractor travel speed in reverse gear exceeds 20 kmph, an audible warning signal on tractor shall get activated. A sticker to the effect that "operating the tractor beyond 20 kmph speed in reverse gear is not safe" should be prominently displayed.	Not fitted (14.09 kmph, 14.31 kmph & 14.75 kmph in 4R gear with 14.9-28, 15.9-28 & 16.9-28 tyre size respectively)	Not applicable		

T-1843/2374/2024	JOHN DEERE, 5050D 4WD V14 TRACTOR- INITIAL COMMERCIAL TEST
	THIS TEST REPORT IS VALID UPTO: 30/04/2029

1	2	3	4	5	6	7	
6.1.7	Labelling of tractors (Provision of labelling plate):						
1)	Make	Evaluative	Should conform to the requirements of CMVR along with maximum PTO Power in kW and year of manufacture in numerical form. <table border="1" style="margin: 5px auto; width: 100px; text-align: center;"> <tr> <td>MM</td> <td>YY</td> </tr> </table> Digit 01 – 12 in box No.1 for MM will represent the months and next two digits in box No.2 for YY will represent the year of Manufacturing.	MM	YY	JOHN DEERE 5050D 4WD V14 11/23 PY3029D7725 12 1PY5050DKPA0 55310 30.3 270	Yes
MM	YY						
2)	Model	Evaluative					
3)	Month & Year of manufacture	Evaluative					
4)	Engine number	Evaluative					
5)	Chassis number	Evaluative					
6)	Maximum PTO power, (kW)	Evaluative					
7)	Specific fuel consumption, g/kWh	Evaluative					
6.1.8	Literature (Submission to test agency):						
(a)	Operator manual	Evaluative	Provided / Not Provided	Provided	Provided	Yes	
(b)	Parts Catalogue	Evaluative	Provided / Not Provided	Provided	Provided	Yes	
(c)	Workshop/ Service manual	Evaluative	Provided / Not Provided	Provided	Provided	Yes	
6.1.9	Fitment of Roll Over Protective Structures (ROPS):						
	For tractor having more than 1150 mm rear track width	Evaluative if fitted	ROPS should meet the requirement of IS:1182 or OECD code or equivalent International Standard	Not Provided	Not applicable		
6.1.10	Standard Accessories	Evaluative	Trailer hitch, front tow hook, linkage drawbar should be provided with tractor	Provided	Yes		
6.1.11	Accessories (optional)	Non Evaluative	Ballast weight, if fitted, should meet the requirement of CMVR	Provided	Yes		

6.2 CATEGORY OF BREAKDOWNS / DEFECTS (As per clause 5.0 of IS:12207-2022):					
S. No.	Category of break-downs	Category (Evaluative / Non Evaluative)	Requirements as per IS: 12207-2022	As observed	Whether meets the Requirements (Yes/No)
1.	Critical	Evaluative	No critical breakdown	None	Yes
2.	Major	Evaluative	Not more than two and neither of them should be repetitive in nature	None	Yes
3.	Minor	Evaluative	Not more than five and frequency of each should not be more than two.	None	Yes
4.	Total breakdowns	Evaluative	In no case, the total number of breakdowns should exceed five, that is, (2 major + 3 minor) or (1 major + 4 minor) or 5 minor breakdowns.	None	Yes

6.3 Conformity with following IS:

- | | | | |
|--------------|---|---|-------------------------|
| i) | Guidelines for declaration of power and specific fuel consumption and labeling of agricultural tractors (First revision) [IS:10273 -1987 (Reaffirmed Year 2019)] | : | Conforms |
| ii) | Agricultural tractors - Rear mounted power take-off - Types 1, 2 and 3 (third revision) [IS:4931-1995 (Reaffirmed Year 2019)] | : | Conforms |
| iii) | Agricultural wheeled tractors – Rear mounted three-point linkage: Part 1 Categories 1, 2, 3 & 4 (fourth revision) [IS:17231 – 2019] | : | Does not conform |
| iv) | Drawbar for agricultural tractors – Link type [IS 12953:1990 (Reaffirmed Year 2022)] | : | Conforms |
| v) | Agricultural tractors- Operator’s seat technical requirement [IS12343 - 2021] | : | Does not conform |
| vi) | Guide for safety & comfort of operator of agricultural tractors:Part 1 General requirements (first revision):[IS 12239 (Part 1) - 2018] | : | Does not conform |
| vii) | Tractors and machinery for agriculture and forestry – Technical means for ensuring safety Part 2: Tractors (first revision) (IS 12239 (Part 2) 1999) (Reaffirmed Year 2019)] | : | Conforms |
| viii) | Guide lines for location and operation of operator controls on agricultural tractors and machinery [IS: 8133 - 2021] | : | Does not conform |
| ix) | Tractors and machinery for agriculture and forestry, powered lawn and garden equipment - Symbols for operator controls and other displays Part -2 Symbols for agricultural tractors and machinery [IS: 6283 (Part-1) - 2006 (Reaffirmed Year 2019) and IS: 6283 (Part-2) – 2007 (Reaffirmed Year 2019)] | : | Does not conform |
| x) | Agricultural Tractors and Machinery - Lighting device for travel on public roads (IS:14683-1999) (Reaffirmed Year 2019)] | : | Conforms |

6.4 Salient Observations:

6.4.1 Operator’s seat:

The following parameters do not meet the requirement of IS: 12343-2021.

- i)** Provision for adjustment of driver’s mass has been specified as 50 to 120 kg against the requirement of 40 to 100 kg.
- ii)** Vertical distance from Seat Index Point to centre of accelerator pedal was measured 505 mm against the requirement of 230 to 460 mm.
- iii)** Width of operator’s seat was measured 440 mm against the minimum requirement of 450 mm.
- iv)** Vertical distance from Seat Index Point to steering control wheel was measured 230 mm against the requirement of 265 to 385 mm.
- v)** Longitudinal distance from Seat Index Point to steering control wheel was measured 395 mm against the requirement of 425 to 525 mm.
- vi)** Vertical distance from Seat Index Point to foot rest was measured 555 mm against the requirement of 450 to 520 mm.

This should be looked into for necessary corrective action.

6.4.2 Operator’s work place:

Spark arrester is not been provided. This should be looked into for necessary corrective action as per the requirement of IS: 12239 (Part-I) 2018.

6.4.3 Three-point linkage:

The dimensions viz. diameter of both upper & lower hitch pin hole, width of ball of lower hitch and leveling adjustment does not meet the requirements of IS: 17231-2019.This should be looked into for corrective action.

6.5 Specification of Tractor

i) Discrepancies in the specification between the Specification sheet and Operator's manual are as under:

S. No.	Description	As per Specification Sheet	As per Operator's manual
a.	Service schedule		
	Engine oil	First change after 100 hours of operation and subsequently after every 250/500 hours of operation.	Change after every 500 hours of operation. (Pg. No. 90-4)
b.	Gear box, rear differential, rear axle, rear final drive, service brakes & steering system.	First change after 1000 hours of operation and subsequently after every 1250 hours of operation.	Change after every 1500 hours of operation. (Pg. No. 90-4)
c.	Front axle & front final drive.	First change after 1000 hours of operation and subsequently after every 1250 hours of operation.	Change after every 500 hours of operation. (Pg. No. 90-4)
d.	Hydraulic	First change after 1000 hours of operation and subsequently after every 1250 hours of operation.	Change after every 1500 hours of operation. (Pg. No. 90-4)

6.6 Maintenance / Service Problems:

No noticeable maintenance or service problem was observed during the test.

6.7 Recommendation with regard to safety on tractor:

- i) Colour codes on illuminated display has not been provided as per the requirement as laid down in IS: 6283 (Part 2): 2007.
- ii) Identification of control lever by colour has not been provided as per the requirement as laid down in Table - 5 of IS: 8133-2021.
- iii) The distance between engine stop control and start control was measured 300 mm against the maximum requirement of 150 mm.
- iv) The working clearance between position control lever & RHS mudguard was measured 45 mm, 2WD/4WD engaging lever & LHS mudguard was measure 40 mm against the minimum requirement of 70 mm.

Above parameters should be looked into for necessary corrective action.

6.8 Adequacy of Literature supplied with machine:

6.8.1 The following literatures were supplied with the test tractor for reference during the test: -

- a) Operator's Manual for John Deere 5036D, 5038D, 5039D, 5039 V3, 5039D V4, 5042D, 5045D, 5050D, 5050 V1, 5050D V8, 5050D V10, 5050D V14, 5050D V15, 5050D 4WD V1, 5050D 4WD V14, 5050 4WD V15, 5105, 5105 V3, 5105 V4, 5205 and 5005 Tractors (India Edition).
- b) Technical Manual for John Deere 5036D, 5038D, 5039D, 5039 V3, 5039D V4, 5042D, 5045D, 5050D, 5050 V1, 5050D V8, 5050D V10, 5050D V14, 5050D V15, 5050D V1 4WD, 5050D 4WD V14, 5050 4WD V15, 5105, 5105 V3, 5105 V4, 5205, and 5005 tractor models.
- c) Parts Catalogue Part-1 & Part-2 for John Deere 5050D 4WD V14 tractor model.




6.8.2 The operator manual may be brought out for the guidance of users and service personnel as per IS: 8132-1999 incorporating, inter alia, the following:

- i) Engine to PTO speed ratio.
- ii) Specification of optional tyres.

T-1843/2374/2024	JOHN DEERE, 5050D 4WD V14 TRACTOR- INITIAL COMMERCIAL TEST
	THIS TEST REPORT IS VALID UPTO: 30/04/2029

TEST CARRIED OUT AT C.F.M.T. & T.I., BUDNI (M.P.), INDIA

TESTING AUTHORITY

B.N. DIXIT AGRICULTURAL ENGINEER	
R.P. PANDEY S.I.E.(TESTING HEAD)	
A. K. UPADHYAY DIRECTOR (I/C)	

Draft Test Report compiled by **Vithato Keyho**, Senior Technical Assistant.

7. APPLICANT'S COMMENTS

Para No.	Our reference	Applicant's comments
7.1	Clause no. 6.4.1 (i) & 6.4.1 (iii).	Your valuable comments and suggestions for improvements are well taken. Under our policy of continuous product improvement these aspects are further being investigated and will try to eliminate these deviations soon wherever necessary.

ANNEXURE-I

TRACTOR RUN HOURS DURING TEST

A.	LABORATORY AND TRACK TESTS:	HOURS
1.	Running-in	Applicant has declared it to be conducted on their work place.
2.	PTO performance test	11.5
3.	Power lift and hydraulic pump performance test	0.9
4.	Drawbar performance test	3.6
5.	Brake performance test	0.7
6.	Nominal speed test	1.2
B.	Miscellaneous test and other run hours including idle run, transportation, trials and preparation for test.	4.9
TOTAL:		22.8