प्रारंभिक व्यावसायिक परीक्षण रिपोर्ट **INITIAL COMMERCIAL TEST REPORT**

संख्या/No. : T-1892/2423/2024 माह/Month : October, 2024

Application Reference No. 28/2023-24/121

(यह परीक्षण रिपोर्ट 31/10/2029 तक वैध है / THIS TEST REPORT IS VALID UPTO 31/10/2029



Model Manufactured by

Make of Agricultural Tractor : ESCORTS KUBOTA LIMITED

- : EURO 50 E14 (BRAND NAME POWERTRAC)
- : M/s. Escorts Kubota Limited, 15/5, Corporate Centre Mathura Road, Faridabad- 121003, Haryana, India



भारत सरकार कृषि एवं किसान कल्याण मंत्रालय (कृषि एवं किसान कल्याण विभाग)

GOVERNMENT OF INDIA MINISTRY OF AGRICULTURE AND FARMERS' WELFARE (DEPARTMENT OF AGRICULTURE & FARMERS WELFARE) केन्द्रीय कृषि मशीनरी प्रशिक्षण एवं परीक्षण संस्थान ट्रैक्टर नगर, बुदनी (म.प्र.) 466 445 **CENTRAL FARM MACHINERY TRAINING & TESTING INSTITUTE** TRACTOR NAGAR, BUDNI (M.P.) 466 445 (An ISO 9001:2015 Certified Institute)

E-mail: fmti-mp@nic.in

Web site: http://www.fmttibudni.gov.in

Telephone: 07564-299003

Page 1 of 32

T-1892/2423/2024	ESCORTS KUBOTA LIMITED, EURO 50 E14 (BRAND NAME - POWERTRAC) TRACTOR, INITIAL COMMERCIAL TEST
	THIS TEST REPORT IS VALID UPTO: 31/10/2029

IMPORTANT INFORMATION

The Government of India, Ministry of Agriculture and Farmers' Welfare has directed, vide an OM No. 13-17/2021-M&T (I&P) dated 28.07.2022, that since 15th August, 2022, only mandatory tests will be carried out on a tractor unless applicant has expressly requested for optional tests as well, mentioned in the above captioned OM.

In the instant case, there is no request from the applicant to carry out the optional tests hence only Mandatory Tests, as given below, have been conducted and reported in this report: -

- **1. PTO performance**
- 2. Hydraulic performance
- 3. Drawbar performance
- 4. Brake performance

1



GOVERNMENT OF INDIA CENTRAL FARM MACHINERY TRAINING & TESTING INSTITUTE TRACTOR NAGAR, BUDNI (MADHYA PRADESH) 466445, INDIA

E-mail: fmti-mp@nic.in

Web site: http://www.fmttibudni.gov.in

Telephone: 07564-299003

ESCORTS KUBOTA LIMITED, EURO 50 E14 (BRAND NAME - POWER TRACTOR, INITIAL COMMERCIAL TEST				
	THIS	TEST REPORT IS VALID UPTO: 31/10/2029		
[C]	Tractor manufacturer's name ar address	nd : M/s. Escorts Kubota Limited, 15/5, Corporate Centre, Mathura Road, Faridabad- 121003, Haryana, India		
[D]	Location of tractor assembly	 i) Escorts Kubota Limited, Plot No. 2 & 3, Sector – 13 Faridabad – 121 007, Haryana, India. ii) Escorts Kubota Limited, 18/4, Mathura Road, Faridabad-121007, Haryana, India. 		
[C]	Submitted for test by (Applicant)	-		
[C]	Selected for test by	: The Ministry vide OM No. 13-17/2021 - M&T (I&P) dated 28.07.2022, has allowed the applicant to submit the test sample directly to the Institute without requiring any random selection for Initial Commercial Testing. Thus, the applicant directly submitted the test sample to the Institute for test.		
[D]	Place of running-in	: At manufacturer's works (M/s. Escorts Kubota Ltd.)		
[D]	Duration of running-in (h):			
	-Engine	: 25		
	-Transmission	: 15		
[C]	Location of test	: Government of India, Central Farm Machinery Training and Testing Institute, P.O Tractor Nagar, BUDNI – 466445 (M.P.), INDIA		
	1. SPECI	FICATIONS OF TRACTOR		
1.1	Identification:			
1.1.1	Denomination			
[C]	Make of tractor	: Escorts Kubota Limited		
[C]	Model (trade name)	: EURO 50 E14 (BRAND NAME - POWERTRAC)		
[C]	Туре	: Rear Wheel Drive, Standard Agricultural Tractor		
[C]	Month & year of manufacture	: 12/23		
[D]	Country of origin	: India		
1.1.2	Numbers:			
[D]	1 st Serial No. of prototype	: T053574504GK		
[C]	Serial No.	: T053682907JM		
		. 100002007000		
1.2 [D]	Engine: Manufacturer's address	: Escorts Kubota Limited, 15/5, Corporate Centre, Mathura Road, Faridabad- 121 003, Haryana, India		
[C]	Make	: Not available		
[C]	Model	: AE3.293A – 3A		
[C]	Туре	: Four strokes, naturally aspirated, liquid cooled, direct injection, diesel engine		
[C]	Serial No.	: E3777551		
1.2.1	Cylinders:	Three (vertical in line		
[C] [D]	Number/disposition Bore / Stroke, (mm)	: Three / vertical, in-line : 101 / 122		
	Capacity, cm ³	: 2934		
[D]				
[D]	Compression ratio	: 17.5 (±5%) : 1 : Overhead, Vertical inline		
[D]	Arrangement of valves			

CENTRAL FARM MACHINERY TRAINING AND TESTING INSTITUTE – BUDNI Page 5 of 32

	ESCORTS KUBOTA LIMITED, EURO 50 E14 (BRAND NAME - POWERTRAC)
T-1892/2423/2024	TRACTOR, INITIAL COMMERCIAL TEST
	THIS TEST REPORT IS VALID UPTO: 31/10/2029

1.	During PTO performance test under natural ambient condition, the power observed	
	in two-hour max. power test was 32.2 kW against the minimum requirement of 32.3	4.5
	kW.as per the requirement of IS :12207- 2022, which does not meet the evaluative	
	requirement. Upon this, the applicant vide letter no. EKL/Hom/R-182, dated	
	10.07.2024 requested following.	
	1. Checking and cleaning of fuel supply line and replacement of fuel filters with	
	new one.	
	2. Replacement of engine oil and engine oil filter.	
	3. Replacement of hydraulic filter.	
	4. Adjustment of fan belt tension.	
	5. Adjustment of clutch free play	
	6. Adjustment of high idle rpm at mid of specified speed.	
	The Request of the applicant was allowed and above-mentioned	
	works were carried out	

6. SUMMARY OF OBSERVATIONS, COMMENTS & RECOMMENDATIONS

6.1 On the basis of test conducted the performance results have been summarized as evaluative (mandatory) / non-evaluative (non-mandatory) parameters applicable for Qualifying Minimum Performance criteria as per Clause-4 (Table-1) of **IS: 12207-2022** for acceptance of the tractor for the purpose of subsidies/NABARD financing are summarized as under:

S. No.	Characteristic	Category (Evaluative / Non-Evalu ative)	Requirements as per IS: 12207-2022	Values declared by the applicant/ (D) Requirement (R)	As observed	Whether meets the require- ments (Yes/No)
1	2	3	4	5	6	7
0.1.1	82979 dated 28 th of <i>A</i> (In the ensuing table, per BIS test code)	August, 2023	Ministry's Office Memorandun 3). applicant's declaration, whereas			. ,
6.1.1 a)	PTO Performance:Maximumpowerunder2 h test,(kW)(Naturalambient condition)	Evaluative	Declared value to be achieved with a tolerance of: $\pm 5\%$ for PTO power and or engine power >26 kW. $\pm 10\%$ for PTO power and or engine ≤ 26 kW.	34.0 (D)	32.7	Yes
b)	Power at rated engine speed, (kW)	Non- Evaluative	-do-	34.0 (D)	32.5	Yes
c)	Specific fuel consumption corresponding to maximum power, (g/kWh)	Evaluative	Should not be more than 10% of declared value	280 (D)	280	Yes
d)	Maximum equivalent crankshaft torque, (Nm)	Non- Evaluative	± 8%	203 (D)	193.5	Yes
e)	Back-up torque, percent	Evaluative	Should be minimum 12 percent	12 (D) 12 (R)	24.8	Yes
f)	Maximum operating te 1) Engine oil	<u>mperature, (^ot</u> Evaluative	C): The declared value should not exceed the <i>Max</i> value specified by the oil company and the observed value under natural ambient/high ambient condition should not exceed the declaration	130 (D)	115	Yes

CENTRAL FARM MACHINERY TRAINING AND TESTING INSTITUTE – BUDNI	Page 26 of 32
---	---------------

	ESCORTS KUBOTA LIMITED, EURO 50 E14 (BRAND NAME - POWERTRAC)
T-1892/2423/2024	TRACTOR, INITIAL COMMERCIAL TEST
	THIS TEST REPORT IS VALID UPTO: 31/10/2029

1	2	3	4	5	6	7
	2) Coolant	Evaluative	Observed value should not exceed the declared value or boiling point of coolant at radiator cap pressure whichever is lower. The boiling point of the coolant at radiator pressure shall be provided by the applicant.	118 (D)	105	Yes
g)	Engine oil consumption, (g/kWh)	Evaluative	Not exceeding 1% of SFC at <i>Max</i> power under natural ambient conditions.	2.80 Maximum (R)	0.29	Yes
h)	Smoke level, m ⁻¹	Evaluative	Maximum light absorption coefficient of 3.25 per meter or equivalent BOSCH No. 5.2 or 75 Hatridge value (As per CMVR).	3.25 per meter Maximum (R)	0.38	Yes
6.1.2	Drawbar performan	ce:				
a)	Max. drawbar pull with ballast corresponding to 15 percent wheel slip, (kN)	Non- Evaluative	Minimum 70% of static mass of tractor with ballast.	*	*	*
b)	Max. drawbar pull without ballast/with standard ballast corresponding to 15 percent wheel slip, (kN)	Evaluative	Minimum 70% of static mass of tractor without ballast or with standard ballast, as the case may be.	14.83 (D) 14.76 (R)	16.51	Yes
с)	Maximum drawbar power without ballast/ with standard ballast, (kW).	Evaluative	Minimum 80 % of PTO power as referred in SI No. i) a) of PTO performance in case of tractors having total static mass > 1500 kg Minimum 75 % of PTO power as referred in SI No. i) a) of PTO performance in case of light weight tractors having ≤1500 kg total static mass of tractor Minimum 75 % of the engine power as referred in SI No. i) a) of engine performance in case of tractors which do not have a PTO shaft.	27.2 (D) 26.2 (R)	28.3	Yes
d)	Maximum transmission oil temperature, (°C) * Applicant vide letter	Evaluative	The declared value should not exceed the maximum value specified by oil company n/R-146 08.05.2024 has requested	130 (D) ed not to cond	88 duct the b	Yes allasted
	drawbar performance test & ten-hour drawbar test which was allowed as per the additional guidelines for testing of tractors as per new regime of testing of tractors vide an OM No. 13-32/2023-M&T(I&P) (FTS-125476) dated 16.05.2023. Accordingly, drawbar performance test under unballasted condition was conducted only.					idelines &T(I&P)
6.1.3	Power lift and hydr					
a)	Maximum lifting capacity At hitch points	Evaluative	the range of lift, (kN): Should not be less than 90% of declared value.	17.65 (D) 15.89 (R) Minimum	18.86	Yes

CENTRAL FARM MACHINERY TRAINING AND TESTING INSTITUTE – BUDNI Page	27 of 32	
--	----------	--

T-1892/2423/2024	ESCORTS KUBOTA LIMITED, EURO 50 E14 (BRAND NAME - POWERTRAC)		
	TRACTOR, INITIAL COMMERCIAL TEST		
	THIS TEST REPORT IS VALID UPTO: 31/10/2029		

1		2	3	4	5	6	7
	2)	With the standard frame		The lift capacity should at least be 24 kg/PTO kW and it should be 21.5 kg/engine	9.00 (D) 7.70 (R)	13.47	Yes
				kW where the tractor is not provided with a PTO shaft.	Minimum		
b)	Maximum drop in the height of the point of application of the force after each 5 minutes interval for a total duration of 30 Minutes, (mm)			The observed value should not exceed 50 mm	50 (D) Maximum	75	NO
6.1.4		e performance at 2					
a)	(m):			e, equal to or less than 600 N o	n brake pe		
	1)	Cold brake	Evaluative	10	10 (R	<i>,</i>	Yes
	2)	Hot brake	Evaluative	10	10 (R	/	Yes
b)	,		Evaluative	Yes / No	Yes	Yes	Yes
6.1.5	optic	onal tests were co		nt has not applied for any o	optional te	sts, there	ore no
6.1.6		ty features:	1				
a)	Guards against moving and hot parts		Evaluative	Belt drives, pulleys, silenc hydraulic pipes [As per 12239 (Part2)]	IS requ	ets the uirement	Yes
b)	Lighting arrangement		Evaluative	As per CMVR		ets the uirement	Yes
c)	Seating requirements		Non Evaluative	Should meet the requirement of IS: 12343 (As amended from time to time)	om me requ	es not eet the iirement	Νο
d)	Technical requirements for PTO shaft		Non- Evaluative	Should meet the requiremend of IS: 4931 (As amended from time to time)	om requ	ets the irement	Yes
е)	Dimensions of three-point linkage		Non Evaluative	Should meet the requiremends of IS: 17231-2019 (amended from time to time)	As me requ	es not eet the iirement	Νο
f)	Specifications of linkage drawbar		Non Evaluative	Should meet the requireme of IS: 12953 (As amended fro time to time)		ets the uirement	Yes
g)	Specifications of Swinging drawbar (wherever fitted)		Non Evaluative	Should meet the requirement of IS: 12362 (Part-3) (amended from time to time)	As	provided	Not appli- cable
h)	Audik on tra	ble warning signal actor	Evaluative	If tractor travel speed reverse gear exceeds kmph, an audible warn signal on tractor shall g activated. A sticker to the effect that "operating the trace beyond 20 kmph speed reverse gear is not safe" sho be prominently displayed.	20 jeget ect itor in	Provided	Not appli- cable

CENTRAL FARM MACHINERY TRAINING AND TESTING INSTITUTE – BUDNI Page 28 of 32

T-1892/2423/2024	ESCORTS KUBOTA LIMITED, EURO 50 E14 (BRAND NAME - POWERTRAC)
	TRACTOR, INITIAL COMMERCIAL TEST
	THIS TEST REPORT IS VALID UPTO: 31/10/2029

6.1.7	Lab	elling of tract	ors (Provision of	labelling plate):			
	1)	Make		Evaluative	Should conform to the requirements of CMVR along-with declared value of PTO in kW, Specific fuel	ESCORT KUBOTA LIM (FORMER ESCORT LIMITED	IITED LY S	Yes
	2)	Model		Evaluative	consumption (SFC) corresponding to maximum	EURO 50 E	É14	Yes
	3)	Month & Yea manufacture	r of	Evaluative	power in g/kWh and year of manufacture in numerical form	12/23		Yes
	4)	Engine numb		Evaluative		E377755		Yes
	5)	Chassis num		Evaluative		T05368290	7JM	Yes
	6)	Maximum P power, (kW)	то	Evaluative	Digit 01-12 in box No. 1 for MM will represent the month and	34		Yes
	7)	Specific fuel consumption g/kWh	,	Evaluative	next two digit in the box No. 2 for YY will represent the year of manufacturing	280		Yes
6.1.8	Lite	rature (Subm	issio	n to test age	ncv):			
(a)		erator manual		Evaluative	The printed literature in booklet	Provideo	b	Yes
(b)	Part	s Catalogue		Evaluative	form should be provided as per	Provided		Yes
(c)		Workshop/ Service manual		Evaluative	IS 8132 and should submit along with the test sample.	Provided		Yes
6.1.9	Fitn	nent of Roll O	ver F	Protective Str	uctures (ROPS):			
	For tractor having more than 1150 mm rear track width		Evaluative	ROPS should meet the requirement of IS:1182 or OECD code or equivalent International Standard	Not fitted		Not Applica- ble	
6.1.10	Standard Accessories		Evaluative	Trailer hitch, front tow hook, linkage drawbar should be provided with tractor	Provideo	d	Yes	
6.1.11	Acc	essories (optio	onal)	Non Evaluative	Ballast weight, if fitted, should meet the requirement of CMVR	app		Not applica ble
6.2	CAT	EGORY OF B	REA	(DOWNS / DE	FECTS (As per clause 5.0 of IS:12	2207-2022):		
S.		Category of		Category	Requirements	As	Whe	ether
No.	b	reak-downs	(E	valuative /	as per IS: 12207-2022	observed	mee	ts the
				Non-		-	Requir	ements
	Evaluative)		valuative)			(Yes	s/No)	
1.	Criti	cal	Evaluative		There is no 'critical breakdown' during the course of testing	None		
2.	Мајо		Evaluative		There are not more than 2 major break downs and neither of them should be of repetitive nature.	None	one Ye	
3.	Mino	or	Evaluative		There are not more than 5 minor defects during the test and neither of them should of repetitive nature.	None	Y	'es
	Tota	I breakdowns	E	Evaluative	In no case, the total number of	None	Y	'es

breakdowns.

break downs should exceed five that is, (2major + 3 minor) or (1 major + 4 minor) or 5 minor

4.

T-1892/2423/2024	ESCORTS KUBOTA LIMITED, EURO 50 E14 (BRAND NAME - POWERTRAC)
	TRACTOR, INITIAL COMMERCIAL TEST
	THIS TEST REPORT IS VALID UPTO: 31/10/2029

6.3 Conformity with following IS:

0.5 60			
i)	Guidelines for declaration of power and specific fuel consumption and labeling of agricultural tractors (First revision) [IS:10273 -1987 (Reaffirmed Year 2019)]	:	Conforms
ii)	Agricultural tractors - Rear mounted power take-off - Types 1, 2 and 3 (third revision) [IS:4931-1995 (Reaffirmed Year 2019)]	:	Conforms
iii)	Agricultural wheeled tractors – Rear mounted three-point linkage: Categories 1N,1,2N, 2, 3N, 3,4N & 4 [IS: 17231:2019]	:	Does not conform
iv)	Drawbar for agricultural tractors – Link type [IS 12953:1990 (Reaffirmed Year 2022)]	:	Conforms
v)	Agricultural tractors- Operator's seat technical requirement [IS12343 - 2021]	:	Does not conform
vi)	Guide for safety & comfort of operator of agricultural tractors: Part 1 General requirements (first revision): [IS 12239 (Part 1) - 2018]	:	Does not conform
vii)	Tractors and machinery for agriculture and forestry – Technical means for ensuring safety Part 2: Tractors (first revision) (IS 12239 (Part 2) 1999) (Reaffirmed Year 2019)]	:	Does not conform
viii)	Guide lines for location and operation of operator controls on agricultural tractors and machinery [IS: 8133 - 2021]	:	Does not conform
ix)	Tractors and machinery for agriculture and forestry, powered lawn and garden equipment - Symbols for operator controls and other displays Part2 Symbols for agricultural tractors and machinery [IS: 6283(Part-1) - 2006 (Reaffirmed Year 2019) and IS: 6283 (Part-2) – 2007 (Reaffirmed Year 2019)]	:	Does not conform
x)	Agricultural Tractors and Machinery-Lighting device for travel on public roads (IS:14683-1999) (Reaffirmed Year 2019)]	:	Conforms

6.4 Salient Observations:

6.4.1 PTO Performance Test:

During PTO performance test under natural ambient condition, the power observed in two-hour max. power test was 32.2 kW against the minimum requirement of 32.3 kW.as per the requirement of IS :12207- 2022, which does not meet the evaluative requirement. Upon this, the applicant vide letter no. EKL/Hom/R-182, dated 10.07.2024 requested following.

- 1. Checking and cleaning of fuel supply line and replacement of fuel filters with new one.
- 2. Replacement of engine oil and engine oil filter.
- 3. Replacement of hydraulic filter.
- 4. Adjustment of fan belt tension.
- 5. Adjustment of clutch free play
- 6. Adjustment of high idle rpm at mid of specified speed.

The Request of the applicant was allowed and above-mentioned works were carried out **Hydraulic Test:**

During the hydraulic lift load maintenance test, the drop in vertical height of the lower link was observed as 75 mm against the maximum permissible limit of 50 mm. This should be looked into for necessary corrective action.

6.4.3 Three-point linkage:

6.4.2

The following parameter does not meet the requirements of IS: 17231-2019 and needs to be looked into for necessary corrective actions:

- i) Diameter of upper hitch point hole and width of ball for upper hitch point have been measured as 25.71 mm and 50.94 mm against the requirement of 19.30 to 19.50 mm and 43.5 to 44.0 mm, respectively.
- ii) Diameter of lower hitch point hole and Width of ball for lower hitch point has been measured as 29.0 mm and 45.0 mm against the requirement of 22.40 to 22.65 and 34.5 to 35.0 mm, respectively.
- iii) Lateral distance from lower hitch point to centre line of tractor has been measured as 364 mm against the requirement of 359 mm.

Therefore, all of the above should be looked into for necessary corrective action.

6.4.4 Operator's seat:

The following parameters do not meet the requirement of IS: 12343-2021.

- i) Provision for adjustment of driver's mass has been specified as 50 to 120 kg against the requirement of 40 to 100 kg.
- ii) Vertical distance from SIP to centre of steering control wheel has been measured as 185 mm against the requirement of 265 to 385 mm.
- iii) Vertical distance from SIP to foot rest has been measured as 590 mm against the requirement of 450 to 520 mm.

Therefore, all of the above should be looked into for necessary corrective action.

6.4.5 Operator's work place:

The following parameters does not meet the requirement of IS: 12239 (Part-I) -2018:

- i) Vertical retainer has not been provided on inner side of clutch pedal.
- ii) Spark arresting device has not been provided in the exhaust system.

Therefore, all of the above should be looked into for necessary corrective action.

6.4.6 PTO master shield:

PTO master shield has not been provided on tractor. This should be looked into for necessary corrective action.

6.5 Maintenance / Service Problems:

No noticeable maintenance or service problem was observed during the test.

6.6 Recommendation with regard to safety on tractor:

- i) Identification of hand controls by colour has not been provided as per the requirement as laid down in Table 5 of IS: 8133-2021.
- ii) Provision for safety starting i.e. provision to prevent the engine starter from engaging has not been provided as per the requirement as laid down in Table 1 of IS: 8133-2021.
 This must be provided to prevent accidents at user level.
- iii) The working clearance around control has been measured as 45 mm against the minimum requirement of 70 mm as per the requirement of IS: 12239 (Part II) 2019.

Above parameters should be looked into for necessary corrective action.

6.7 Specification:

- i) Opening pressure of cylinder safety valve is not announced. It must be announced. Change of engine oil is recommended as 50 hours and subsequently after 500 hours of operation in specification whereas it is recommended in operator manual as 50 hours and subsequently after 300 hours of operation. It should be looed into for corrective action.
- ii) Change of gear box housing oil is recommended after 1200 hours specification sheet whereas in operator's manual is recommended after 900 hours. It may be looked into for corrective action.
- iii) Make of the engine is declared as Escorts Kubota Limited in specification whereas there is no embossing or labelling plate with such name on engine. It should be looked into for corrective action.
- iv) Brake oil capacity is mentioned in the application as "NA" whereas the brake oil is common with transmission oil. It should be looked into for corrective action.

6.8 Adequacy of Literature supplied with machine:

- The following literatures were supplied with the test tractor for reference during the test:
 - i) Operator's Manual for "Escorts Kubota Limited, EURO 50 E14 (BRAND NAME POWERTRAC), and EURO 60 E5 (BRAND NAME FARMTRAC)", tractor models.
 - ii) Parts Catalogue for "Escorts Kubota Limited, EURO 50 E14 (BRAND NAME POWERTRAC)" tractor model.
 - iii) Service manual for "Escorts Kubota Limited EURO 50 E14 (BRAND NAME POWERTRAC)" tractor model.
- **6.8.1** The operator manual may be brought out for the guidance of user's and service personnel as per IS:8132-1999 incorporating, inter alia, the following:
 - i) Safe hitch height while using trailer.
 - ii) Recommended ballast masses for different operations.

CENTRAL FARM MACHINERY TRAINING AND TESTING INSTITUTE – BUDNI Page 31 of 32

	ESCORTS KUBOTA LIMITED, EURO 50 E14 (BRAND NAME - POWERTRAC)			
T-1892/2423/2024	TRACTOR, INITIAL COMMERCIAL TEST			
	THIS TEST REPORT IS VALID UPTO: 31/10/2029			

iii) Literature should be brought out in national as well as other regional languages of india for the guidance of user.

TEST CARRIED OUT AT C.F.M.T. & T.I., BUDNI (M.P.), INDIA

TESTING AUTHORITY

SHIVKUMAR SHARMA AGRICULTURAL ENGINEER	Stor
V.S. SHINDE SENIOR AGRICULTURAL ENGINEER	the torinstry
Dr. P. P. RAO DIRECTOR	P. P. Raci

Draft Test Report compiled by: Dharmendra Kumar, Senior Technical Assistant

7. APPLICANT'S COMMENTS

Para No.	Our reference	Applicant's comments
7.1	6.3 (iii, v, vi, viii & ix)	Observation will be studied, and necessary corrective action will be initiated

ANNEXURE - I

TRACTOR RUN HOURS DURING TEST

Α.	LABORATORY AND TRACK TESTS:	HOURS
1.	Running-in	Applicant has declared that it has already been conducted at manufacture's work place.
2.	PTO performance test	15.0
3.	Power lift and hydraulic pump performance test	1.2
4.	Drawbar performance test	4.0
5.	Brake performance test	1.3
6.	Nominal speed test	0.5
В.	Miscellaneous test and other run hours including idle run, transportation, trials and preparation for test	8.9
	TOTAL:	30.9

CENTRAL FARM MACHINERY TRAINING AND TESTING INSTITUTE – BUDNI Page 32 of 32